



## TDS for Fafix Flooring white paste adhesive

	<p><b>Product description</b>  <b>FAFIX</b> white paste adhesive is a water base adhesive based on water base resin and polymers.</p>
<p><b>applications</b></p>	
<p>It is suitable for all type of tiles and flooring elements such as PVC tile, vinyl tile, neoprene tile, moquette, stone, ceramic and so on at surfaces such as cement surfaces, ceramic, gypsum, glass and many polymeric surfaces at industrial, gym, general and domestic buildings without any fire, explosion or respiratory hazard.</p>	
<p><b>properties</b></p>	
<p>It is odorless, free from organic solvents, without any fire an explosion hazard and environment friendly..</p>	
<p><b>How to use</b></p>	
<p><b>1-Surface preparation</b>  Surfaces must be clean, leveled, without any greases and germs. For leveling can use usual building material such as cement.  Adhesive is naturally gap filling but for crevice and whole surfaces caused increasing on adhesive consumption.  For surfaces with high porosity and water absorption first uses a primer from diluted adhesive.</p> <p><b>2-Environment conditions:</b>  Environment temperature must be at least 18 degree centigrade and for cold conditions warm up environment before using adhesive. Best temperature is 18-30 degree centigrade.</p> <p><b>3-Gluing surfaces:</b>  Before using adhesive mix all container and apply adhesive on surfaces by a v notch knife depends on surrounding conditions after 5-20 minutes adheres tiles and wait for at least 24 hr. for good adhesion. Curing will be completed after 72hr.  For water absorber tiles dilute adhesive by water.  Suitable v notch knife is 1.5 mm depth and 5 mm in length.</p>	
<p><b>Technical specifications</b></p>	
<p><b>Appearance :</b> white viscose paste  <b>Color :</b> white  <b>Odor :</b> not available  <b>Odor threshold :</b> not available  <b>PH :</b> 8-10  <b>Boiling point :</b> 100 degree centigrade  <b>Freezing point :</b> 0 degree centigrade</p>	
<p><b>storage</b></p>	
<p>Keep container tightly at 5-30 degree centigrade and keep from direct sun light, children and freezing. Storage life is 12 month.</p>	
<p><b>How to clean</b></p>	



Use wet clothes for cleaning fresh adhesive. For cleaning after 24 hr. use ethanol.  
For any question please contact Fars Chasb engineering team

**packaging**

10 kg PE drum  
4 kg PE drum  
1kg PE drum

**Our advice is based on extensive research and practical experience. However cause of the large variety of materials and the conditions under which our products are applied. We assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.**

**This document prepared at Fars Chasb Company and included of legal rules you can refer to this document but must write our company as source of document.**

Shahrak sanaati ab barik farschasb co. Iran – Shiraz

Tel: +98-71-32602400

Fax: +98-71-32602145

[www.farsadhesive.com](http://www.farsadhesive.com)